


## Wiring Diagram I Intelligent LED Driver/Controller

Up to 60Vdc, Programmable Output Current, Max 50W & Max 100W

**Input Voltage: 110 - 277 Vac**

Max Connected LOAD: 50W or 100 W



**Note:**

\* Each channel needs to be programmed, default at 350mA\*

\*\* All 4 channels of the driver are independent but have the same programmed OUTPUT CURRENT\*\*

**WARNING:**

CONNECTION OF LUMINAIRE TO POWERED DRIVER WILL RESULT IN PERMANENT DAMAGE TO THE LED AND VOIDED PRODUCT WARRANTY.

EACH OF THE LED OUTPUTS ON DMX DRIVER ARE INDIVIDUAL CHANNELS & POLARITY MUST BE FOLLOWED.

4/20/21

\*Illustration is for example purposes only. Components may vary depending on technical requirements of the light.\*

101 North Garden Avenue • Clearwater, Florida 33755 USA • P 727.213.0410 • Support@ZaniboniLighting.com

The manufacturer reserves the right to change or modify the design, dimensions and specifications at any time without notice.

The manufacturer accepts no liability for consequential damage which is occasioned to the user based on the data provided.

For more information contact your representative or go to [ZaniboniLighting.com](http://ZaniboniLighting.com).